



Thank you for purchasing KC HiLiTES products; your satisfaction is very important to us. If you have any questions regarding this product or any other KC HiLiTES products, please contact us at (888) 689-5955 or visit [kchilites.com](http://kchilites.com).

#### Parts Included:

(1) Wire Harness, (1) Switch, (8) Wire Ties

#### 1. Mounting Your Lights:

After choosing a location to mount your lights, install and loosely tighten before installing the wiring harness. *Optional:* Refer to 'Template' for Flush Mount applications.

#### 2. Wiring Your Lights:

1. Begin by routing the KC wire harness from the battery (or power source) and connect the light leads (DT connectors) to the lights. Next, route the three switch leads (spade connectors) toward the desired switch location.

2. To install the switch, drill a  $\frac{3}{8}$ " hole in the desired location to press the switch into.

(**Note:** Do not install switch until you have the switch wires routed to the switch location, and then attach the switch wires accordingly before pressing the switch into the mounting hole). Connect the switch wires as follows: **Black wire** to Ground (brass color) blade, **Red wire** to Load (center) blade, and **Yellow wire** (Supply) to the last blade on the switch.

Complete switch installation and place switch in **Off** position.

3. Next, connect the **Yellow Power** lead (with ring terminal) to the (+) Positive side of the battery or power source. Connect the **Black Ground** lead (with ring terminal) to the (-) Negative side of the battery or chassis ground. Test your lights.

#### 3. Securely tighten your lights after installation.

