

MATERIAL SAFETY DATA SHEET - 8 Point

SECTION 1 – PRODUCT INFORMATION

Mascoat
Houston, TX 77041

Emergency phone: (713) 465-0304
Fax: (713) 465-0302
Date Reviewed: June 2011

Product Name: LizardSkin Ceramic Insulation
Product ID: LSCI
Common Chemical Name: Acrylic Insulation Emulsion
Synonyms: None
Molecular Formula: Mixture

Thermal Insulating Material

HEALTH	1
---------------	----------

FLAMMABILITY	1
---------------------	----------

PHYSICAL HAZARD	0
------------------------	----------

Personnel Protection	G
-----------------------------	----------

Eye protection
Gloves
Dust mask

SECTION 2 – HAZARDOUS INGREDIENTS DETERMINED BY OSHA by PERCENTAGE

<u>Cas Number</u>	<u>Ingredients</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
	NONE			

SECTION 3 – PHYSICAL PROPERTIES

Color:	White, Black	Form/Appearance:	Thick emulsion mixture
Odor:	Slight ammonia	Melting Point:	N/A
Boiling Point:	No boiling point	Evaporation Rate (Butyl Ace =1):	<1
Freeze Point	32°F (0°C)	Solubility in H2O:	Dilutable
Specific Gravity:	0.670	Volume Solids:	70.6%
Pounds/Gallon:	5.59	VOC Content:	0.07 lbs/gal
Non Volatile Solids (weight):	56.3%		

SECTION 4 – FIRE FIGHTING MEASURES

Flash Point: Noncombustible

Auto ignition: N/A

Extinguished Media: (for dried film) carbon dioxide, dry chemical, or alcohol foam.

Special Fire Fighting Procedures: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure buildup.

Unusual Fire and Explosion: Product will not burn but may spatter if temperature exceeds boiling point. Extreme heat may cause closed containers to burst. Dried film of product is capable of burning giving off oxides of carbon/nitrogen.

SECTION 5 – REACTIVITY DATA

Stability Data: Stable

Incompatibility: Solvents will coagulate the product.

Conditions or Hazards to Avoid: Extreme temperatures above 500°F (260°C)

Hazardous Decomposition: Hazardous polymerization will not occur.

Corrosive Properties: Not corrosive

Oxidizer Properties: Not an oxidizer

Chloride Properties: None

SECTION 6 – HEALTH HAZARD AND FIRST AID DATA

Routes of entry: skin-possible ingestion-possible inhalation-possible

Health Hazards Acute – In a confined area, vapors in high concentration may bother personnel.

Carcinogenicity: N/A

SECTION 6 – HEALTH HAZARD AND FIRST AID DATA (cont)

First aid procedure:	Eye exposure - flush eyes with water immediately. Get immediate medical attention. Skin contact - wash area with soap and water. If redness persists, seek medical attention Ingestion – If swallowed, dilute with water. DO NOT INDUCE VOMITING. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Get immediate medical attention. Inhalation – Move to fresh air. Aid in breathing if needed and get immediate medical attention. Notes to Physicians – none known. Aggravated Medical Attention – No data is available at this time which addresses medical conditions that are generally recognized as being aggravated by exposure to this product. Please refer to the effects of overexposure section for effects (if any) observed in animals. Special Precautions – No
-----------------------------	--

SECTION 7 – ACCIDENTAL RELEASE MEASURES

Steps if material is released:	Spills should be contained and placed in suitable containers for disposal by a licensed facility.
Waste Disposal Methods:	Waste from this material is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed containers. Dispose of in accordance with Federal, State, and Local regulations.
Precaution in handling and storage:	Use only with adequate ventilation. Avoid breathing vapor directly and spray mist directly. Avoid direct contact with eyes. Wash hands after using. Protect against dust which may be generated by sanding or abrading the dried film.
Other Procedures:	Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. <i>Keep out of reach of children.</i>
General:	Protect from freezing.
Other:	Keep out of direct sunlight in storage area

SECTION 8 – PERSONNEL PROTECTION

Clothing:	Coveralls or an apron recommended.
Respiratory Protection:	Ventilation and dust mask recommended during application. If sprayed in confined area with little ventilation, respiratory equipment may be preferred due to slight ammonia odor and to help drying process.
Ventilation:	Local exhaust - <i>preferable</i> Mechanical (gen) - <i>acceptable</i>
Protective Gloves:	Preferred.
Eye Protection:	Spectacles with unperforated sideshields.
Other Protective Equipment:	None needed.

OTHER

Special Handling:	DO NOT LET PRODUCT FREEZE.								
Hazardous ratings:	Mascoat currently uses the National Paint and Coatings Association rating system. The use of an asterisk (*) in the HMIS rating indicates the potential for chronic health effects								
HMIS:	<table><thead><tr><th>Health</th><th>Fire</th><th>Reactivity</th><th>Special</th></tr></thead><tbody><tr><td>1</td><td>1</td><td>0</td><td>0</td></tr></tbody></table>	Health	Fire	Reactivity	Special	1	1	0	0
Health	Fire	Reactivity	Special						
1	1	0	0						
Hazardous rating OSHA:	The product is considered NON HAZARDOUS by the OSHA Hazard Communication Standard.								
Trademark:	LizardSkin is a registered trademark of Mascoat, Houston, TX USA.								
Important:	While descriptions, designs, data and other information contained herein are presented in good faith and believed to be accurate, it is provided for guidance only. Many factors may influence the processing or application/use. Mascoat recommends that tests are made for the suitability for the product in the intended purpose. The intended use of this document is for health and handling procedures and not intended for an ingredients list for reformulation.								
Shipping:	This product is acceptable for shipment as non-hazardous via motor, air or ocean freight without any specialized handling. (Class 55).								