



## Mustang Trim Panel

Read All Instructions Prior to Installation

Check all parts for defects or burrs and fit before installing

# 1999-2004 Mustang Trim Panel Installation

### Component List:

Trim Panel

1. Remove license plate.
2. Remove the Ford oval and GT emblems from the trunk lid. Use a heat gun or hair dryer to heat the two-way bonding tape on the backside of the emblems, be careful not to damage paint.
3. Clean areas where Trim Panels mount to car. Wipe these areas with Isopropyl Alcohol to remove any wax in the area and allow to dry.
4. Test fit the trim panels.
5. Starting with the center section, peel the red backing from the attaching tape lightly place panel onto car, check alignment and adjust if necessary. Press on panel above the tape to seal the tape to the vehicle.
6. Repeat for the side panels.

7. Re-install the Ford oval and the GT emblems to the trim panels in their respective recesses. If the tape on the backside of the emblems is damaged, you can purchase automotive acrylic bonding tape at your local auto parts store and re-tape the emblems before reapplying them.
8. Reinstall you license plate.

[www.classicdesignconcepts.com](http://www.classicdesignconcepts.com)

1880 W. West Maple Walled Lake, MI 48390

Questions? Call 248-624-7997 or email [questions@classicdesignconcepts.com](mailto:questions@classicdesignconcepts.com)